

**1: SPORTING REGULATIONS - GENERAL****1.1: TITLE & JURISDICTION:**

The **TOYOTA MR2 CHAMPIONSHIP** is organised and administered by the 750 Motor Club Ltd in accordance with the National Competition Regulations (NCR's) and incorporating the provisions of the International Sporting Code of the FIA) and these Championship Regulations.

1. **MOTORSPORT UK Championship Permit No: CH2026/029**
2. **MOTORSPORT UK Championship Grade: C.**
- 3: **Race Status:** Inter-Cub.

This document defines the specific Championship regulations and structure of the Championship for both fair and safe competition and are to be adhered to by all Entrants and Drivers at all times.

The Organisers reserve the right to amend or clarify these Championship Regulations at any time during the season by way of publication of Official Championship Bulletins issued in accordance with NCR Ch. 3 App. 10 Art 4.2 and subject to Motorsport UK approval.

**1.2: OFFICIALS:**

1. **Championship Co-Ordinator:** G.Groombridge, Donington Park, Castle Donington, Derbyshire, DE74 2BN  
① 01332 814548; 📧 giles@750mc.co.uk
2. **Championship Eligibility Scrutineer(s):** S. Dockray, Deputy : B.Blackmore
3. **Championship Stewards:**  
T. Gregory                      C. Emmerson                      I.Sowman                      T.Stevens

Any three Championship Stewards will constitute a quorum. In the event of any of the Championship Stewards listed above being unavailable or being unable to consider any particular matter due to a perceived conflict of interest, the organisers reserve the right to appoint an alternative Championship Steward or, if deemed to be necessary, more than one alternative Championship Steward.NCR Ch.4 App.1 Art.1.2. The Championship Stewards can only adjudicate upon any disputes irregularities or appeals arising from the published Championship Regulations. They are also empowered to consider any request from the Championship Coordinator to penalise any Competitor for any breach of Championship Regulations and after holding a formal hearing those Stewards may impose a penalty in accordance with NCR Chapter 2 subject to the rights of Appeal to the National Court.

**1.3: COMPETITOR ELIGIBILITY:**

- 1 Entrants must:
  - (a) be fully paid up valid members of the 750 Motor Club and
  - (b) be Registered for the Championship and
  - (c) be in possession of a valid MOTORSPORT UK Entrants Licences.
- 2 Drivers and Entrant/Drivers must:
  - (a) Be current Members of the 750 Motor Club and
  - (b) be Registered for the Championship and
  - (c) be in possession of valid Competition (Racing) Club Licence, as a minimum
  - {d) Or be in possession of the highest grade of national Race licence or valid FIA International Licence including confirmation of a valid medical certification, together with their ASN's written consent (Motorsport UK National Competition Rules (NCR) Ch.6 App.3 Art.1 and FIA ISC Article 2.3.7.b applies)
  - (e) If participation in the Championship requires absence from education a driver, in full time school education is required to have the approval of their head teacher and a letter stating such approval from their school in order to fulfil registration for the Championship. A driver shall not take time out of their education to participate in motor sport without the prior written approval of their education establishment.
3. All necessary documentation must be presented for checking at all rounds when signing on. All competitors must sign-on at Events that they compete in and all necessary documentation must be available to be presented for checking at all times upon the demand of the Officials.

**1.4: REGISTRATION:**

1. All competitors must register for the championship by returning the Registration Form with the Registration Fee to the Coordinator prior to the Final Closing date for the first round being entered.
2. The Registration Fee for the season is **£160-£165** payable upon registration. For competitors wishing to enter a single event a registration fee of £35 is payable and points will be awarded for this event. If further races are entered



the balance of the ~~£160~~ £165 fee must be paid.

3. Registration numbers will be the permanent Competition number for the Championship.

### 1.5: CHAMPIONSHIP ROUNDS:

The TOYOTA MR2 CHAMPIONSHIP will be contested over the following rounds\*:

Date	Circuit	Round/s
6 April	Donington Park	2
10 May	Silverstone Nat	2
21 June	Snetterton 300	2
19 July	Cadwell Park	2
8 August	Brands Hatch	2
26 September	Thruxton	2
17 October	Donington Park	2

*\* subject to valid track licences being in place*

If a minimum of 16 entries is not reached by close of entries, the Organisers reserve the right to amalgamate races/classes or cancel races.

### 1.6: SCORING:

1. Both Overall and Class Points will be awarded to Competitors listed as classified finishers in the Final Results as follows:- P1 = 50 points, P2= 47 points, P3 = 45 points with subsequent finishing positions decreasing by 1 point until P45 = 3 points. All other finishers 2. All starters who fail to finish 1. Fastest Lap 1 Point.

2. The totals from all qualifying rounds run (excluding any races which are abandoned and which are not replaced) less 2 will determine the final championship points positions.

3. Ties shall be resolved using the formula in NCR Ch.4 App.3.

4. Where the race distance has been reduced (2.6.) it shall still count as a full points scoring round.

5. Competitors not registered for the Championship may be permitted on an individual round basis and will:

(a) be deemed "Guest Competitors"

(b) not score points and for the purpose of points scoring will be ignored

(c) qualify for Event awards

(d) comply with the eligibility criteria as prescribed in Article 1.3. above, with the exception of 1.3.1. (b) and 1.3.2.

(b), as appropriate

~~6. Where two drivers are registered in the Team Challenge and are sharing a car, their points scored (as per 1.6.1) will be combined and they will compete for the Team Challenge Awards as per 1.7.3. Each driver must contribute at least 4 scores to the team total.~~

### 1.7: AWARDS:

1. All awards are to be provided by the Organising Club unless agreed otherwise.

2. Per Round: Trophies to 1st, 2nd and 3rd in each class.

3. Championship: Trophies, subject to a minimum of 5 race starts, to:-

1st 2nd, 3rd overall and 1st, 2nd, 3rd in each class.

Best Prepared car.

Highest Placed Novice (one who has not held a MOTORSPORT UK Race Licence prior to the current season).

~~Team Challenge trophy for the team with the highest scores as described in 1.6.6.~~

4. Presentations: Awards will be presented at the end of each event, and/or at the end of the Championship at the designated presentation ceremony.

5. Entertainment Tax Liability: {deleted}

6. If Provisional Results or Championship Tables are revised after any presentations and these revisions affect the distribution of awards the Competitors concerned must return them to the organisers in good condition within 7 days.

## 2: CHAMPIONSHIP EVENTS & RACE PROCEDURES

### 1. ENTRIES:

1. Competitors are responsible for sending in correct and complete entries with the correct entry fee prior to the closing date for entries before each event.

2. Incorrect or incomplete entries (Including Driver to be Nominated Entries) are to be held in abeyance until they



are complete and correct and the date of receipt for acceptance of entry purposes shall be the date on which the Event Organiser receives the missing or corrected information or fee.

3. Any withdrawal of Entry or Driver/ Car changes made after acceptance of any entry must be notified to the Event Organisers in writing. NCR Ch.3 App.11 Art.1.1 applies.

4. The Entry Fee for each event shall be specified in the SRs and on the entry form.

5. Reserves will be listed in the Final List of Entries published with Final Instructions or in a Bulletin.

**2. BRIEFINGS:** Organisers will notify Competitors of the times and locations for all briefings in the Final Instructions for the Events. Competitors must attend all briefings. Any Written briefing is an Official Document.

### 3. QUALIFICATION PRACTICE:

1. Should any Practice session be disrupted the Clerk of the Course shall not be obliged to resume or re-run the session; the decision of the Clerk of the Course shall be final.

2. Each driver ~~shall~~ **must** complete a minimum of 3 laps in the car to be raced, and in the correct session, in order to qualify NCR Ch.12 App.6 Art.3.1 applies.

3. Where practical, competitors will be released for qualifying in overall Championship points order. For the first race of the season, the previous year's overall Championship table will be used. Competitors that do not appear on the overall Championship table will be released after all other competitors in a random order determined by the Championship Co-ordinator. Any competitor who does not arrive in the assembly area in time to assume their allocated position or who elects not to do so will be released after all other competitors.

**4. RACES:** Should any race be disrupted the Clerk of the Course shall not be obliged to resume or rerun the race NCR Ch.12 App.6 Art.9 applies (see 1.6.4. above applies)

### 5. STARTS:

1. All cars will be released to form up on the grid prior to the start in formation as specified on the grid sheet.

2. The start will be via Standing start. The minimum Countdown procedures/audible warnings sequence shall be:-

I. 1 minute to start of Green Flag Lap - Start Engines/Clear Grid.

II. 30 Seconds - Visible and audible warning for start of Green Flag Lap.

III. A five second board will be used to indicate that the grid is complete.

IV. The red lights will be switched on five seconds after the board is withdrawn.

3. Any car removed from the grid after the 1 minute stage or driven into the pits on the Green Flag lap shall be held in the pitlane and may start the race after the last car has passed the start line or pitlane exit, whichever is the later to take the start from the grid.

4. Any driver unable to start the Green Flag Lap or start are required to indicate their situation as per NCR Ch.12 App.6 Art. 6.11. In addition, any driver unable to maintain grid positions on the Green Flag Lap, to the extent that ALL other cars are ahead of them, may complete the Green Flag lap but MUST remain at the rear of the last row of the grid but ahead of any cars to be started with a time delay.

5. In the event of any starting lights failure the Starter will revert to use of the National Flag.

**6. SESSION RED FLAG:** Should the need arise to stop any race or practice, RED LIGHTS will be switched on at the Start line and RED LIGHT PANELS / FLAGS will be displayed at the Start line and at all Marshals Signalling Points around the Circuit. This is the signal for all drivers to cease circulating at racing speeds, to slow to a safe and reasonable pace and to return to the pit lane, during practice, and to the starting grid area, during a race, unless otherwise directed by officials. Cars may not enter the Pits unless directed to do so. Work on cars already in the Pits must cease when a race is stopped. Marshals should revert to displaying yellow flags to indicate to Drivers the particular location of any incident hence supplementing the Light Panels

### 7. PITS, PADDOCK & PITLANE SAFETY:

1 Pits & Paddock: Competitors must ensure that the MOTORSPORT UK, Circuit Management and Organising Club Safety Regulations are complied with at all times.

2. Pitlane: The outer lane or lanes are to be kept unobstructed to allow safe passage of cars at all times. The onus shall be on all Drivers to take all due care and respect the pit lane speed limits.

3. Refuelling: May only be carried out in accordance with the requirements of NCR Ch.12 App.11 Art.2, the Organising Club Regulations, Circuit Management Regulations and the SRs or Final Instructions issued for each Circuit/Event.

4. Speed Limit: Pit Lane Speed Limit will be 60 km/h or as notified in the Final Instructions or Bulletin for the Event

**8. RACE FINISHES:** After taking the Chequered Flag drivers are required to:



- I. progressively and safely slow down
- II. remain behind any competitors ahead of them,
- III. return to the Pit Lane Entrance/Paddock Entrance as instructed,
- IV. comply with any directions given by Marshals or Officials
- V. keep their helmets on and harnesses done up while on the circuit or in the pitlane.

**9. RESULTS:** All Practice Timesheets, Grids, Race Results are to be deemed Provisional until all vehicles are released by Scrutineers after Post Practice/Race Scrutineering and/or after completion of any Judicial or Technical Procedures. (NCR Ch.3 App.6 Art.1.4.)

**10. TIMING MODULES:** The 750 Motor Club utilises transponder-based timing and competitors must have a compatible transponder fitted and working and advise the race organisers of its number prior to the event. Compatible transponders include the AMB TRANX 260 and MyLaps X2 & TR2 models.

**11. QUALIFICATION RACES:** If any event is oversubscribed the Organising Club may at their discretion run Qualification Races.

**12. OPERATION OF SAFETY CAR:** The Safety Car will be brought into operation and run in accordance with NCR Ch.12 App.8 Art.2.

**13. ONBOARD CAMERAS:** All competitors are required to carry an on board, in car camera that records to an SD (or micro-SD) card that must be capable of recording HD footage that can be played back on a standard laptop. Recordings from the cameras may be used where there is an incident which is subsequently brought before the Clerk of the Course for investigation.

It is the competitor's sole responsibility to ensure safe installation and effective operation of the camera equipment. At all times cameras must be fitted in accordance with with Motorsport UK National Competition Rules and be approved by the Chief Scrutineer in accordance with NCR Ch.7 App.9 Cameras must be mounted in a position such that the steering wheel and track in clear view. The unit must always be switched on and be recording when the car is on track during any official free practice, qualification session and race.

The onus is on the competitor to ensure that the camera unit battery is charged, the camera switched on to record and ensure the SD card has enough capacity to record the above-mentioned sessions. The SD card must ONLY contain the files from the event in question. Penalties as below apply.

In the event that no recording is available when requested by the Organisers or Clerk of the Course for judicial purposes then warnings will be issued by the Clerk of the Course for the 1st and 2nd offences which will as a consequence incur the following championship penalties. then the following penalties will be applied by the Clerk of the Course.

- a. First offence – ~~Championship Reprimand~~ **Two Championship Points Deducted**
- b. Second Offence – ~~Four~~ **Four Championship Points Deducted** ~~– Equivalent to a 5<sup>th</sup> an 8<sup>th</sup> place finish.~~
- c. Third Offence - Disqualification.

### 3: SPECIFIC CHAMPIONSHIP REGULATIONS

1. By registering for the Championship all competitors and their associates commit to positively promote and demonstrate the Motorsport UK's Respect Code.

Where any reports of disrespectful conduct are judged to be well founded the Championship organisers may issue warnings or require remedial actions and/or report the matter to the Championship Stewards who may impose appropriate penalties which can include loss of Championship points and/or race bans through to Championship Expulsion and referral to Motorsport UK.

It is imperative that we promote the safety and wellbeing of young people and adults at risk. In addition to this all participants must be aware of their behaviour and conduct at all times and abusive language and harmful behaviour will not be tolerated. Any such incidents must be reported to the Championship Coordinator and/or Safeguarding Officer who will also relay the report Motorsport UK. Details of the Motorsport UK Policies and Guidelines are



available at [www.motorsportuk.org/resource-centre](http://www.motorsportuk.org/resource-centre) by selecting Policies and Guidelines.

2. In the event of any rounds being oversubscribed the Organising Club may, in liaison with the Championship Coordinator, at their discretion run Qualification races as per 2.11 of these regulations. Alternatively at double header race Events, should there be sufficient space within the timetable, the Organising Club may divide the grid after qualifying into 3 separate Groups. The Groups will then form 3 races whereby each competitor participates in two races. All 3 races will be eligible for full championship points.
3. In the event that a qualifying session is oversubscribed and a second exclusive session is available then the number of competitors in each session will be split equally based on their position in the current overall Championship table. In the case of the first race of the season, the previous year's overall Championship table will be used. Any competitor who does not feature on the Championship table will be allocated in the first session with the remaining places assigned in descending order. All other competitors will be allocated in the second session.
4. In the event that a qualifying session is oversubscribed and a second exclusive session is not available, competitors may be required to qualify with another formula. In this instance, the drivers to qualify out of the main session are selected in reverse order from the current overall Championship table. In the case of the first race of the season, the previous year's overall Championship table will be used. Any competitor who does not feature on the Championship table will be allocated in the main session.
5. In all eventualities, a competitor who qualifies in a session other than allocated will be required to start from the back of the grid.
6. At each Round of the championship Race 1 grid positions will be determined by each competitors fastest lap time in Qualifying. Grid positions for any subsequent races at the same Event will be determined by the fastest lap time in the preceding race.

#### 4: SPECIFIC CHAMPIONSHIP PENALTIES:

In accordance with NCR Chapters 2 & 12 and additionally:

##### 4.1: INFRINGEMENT OF TECHNICAL REGULATIONS:

1. Arising from post practice Scrutineering or Judicial Action: Minimum Penalty: The provisions of NCR Ch.2 App.8.
2. Arising from post-race Scrutineering or Judicial Action: Minimum Penalty: The provisions of NCR Ch.2 App.8.
3. For infringements deemed to be of a more serious nature the Clerk of the Course ~~will~~ may invoke the provisions of NCR Ch.2 App.8 Art.2

##### 4.2: ADDITIONAL SPECIFIC CHAMPIONSHIP PENALTIES

###### ~~1. NCR Ch.2 App.8 and may impose the penalty set out in NCR Ch.2 App.8 Art.2~~

2. In order to maintain standards of conduct, the Championship Organisers will monitor all Officials/Observers reports of adverse behaviour at race Events. If any individual is included on two such reports during one racing season the Championship Organisers will request the Clerk of Course at future race Events to consider specific observation of that driver's conduct.
  3. The Clerk of Course may impose a "Stop-Go" or "Drive through" penalty during a race in accordance with NCR Ch.12 App.10 Art.2.
  4. Championship Stewards are also empowered to consider any request from the Championship co-ordinator to penalize any Competitor for any breach of Championship regulations and, after holding a formal hearing if they deem it necessary, to impose a penalty in accordance with NCR Ch.2 App.2 Art.4 (subject to the rights of appeal provided for in NCR Ch.2 App.5 Art.1)
  5. One or more of the following may be imposed by the Championship Stewards as appropriate;
    - a) Reprimand
    - b) Fine. This may be also applied in the case of a driver receiving three reprimands from the Championship Stewards in one season.
- ~~e) Time or Grid Penalties~~
- ~~d) Suspension from all or part of the Championship. This may also be applied in the case of a driver receiving two fines from the Championship Stewards in one season. Disqualification from further participation in the Championship, NCR Ch.2 App.2 Art 4.1~~



## 5: TECHNICAL REGULATIONS

### 5.1: INTRODUCTION:

a) The following Technical Regulations are set out in accordance with the MOTORSPORT UK specified format and it should be clearly understood that if the following texts do not clearly specify that you can do it, you must work on the principle that you cannot. The fact that some modifications are mentioned as prohibited does not imply that others are allowed.

b) **STANDARD:** The word 'standard' used within these technical regulations as a description of components is to be interpreted as per 'Standard Part' defined in NCR Ch.1 App.1. Checking will be by comparison to spare parts supplied by the manufacturer's official agent or by any other means necessary to ensure compliance. It applies to the specified component/s from the manufacturer's parts list for the model / engine shown on the entry form or registration form. No modifications permitted beyond the repair or adjustment processes specifically specified by the manufacturers' workshop manual or microfiche.' Checking will be by comparison to spare parts supplied by the manufacturer's official agent or by any other means necessary to ensure compliance. Where specifications for parts (e.g. camshaft, final drive, gear ratios, anti-roll bars etc) are stated within table 6.3 of these regulations, they are mandatory for that make and model of car.

c) **STANDARD PATTERN:** The words 'standard pattern' used within these technical regulations as a description of components is to be interpreted as per 'Standard Pattern Part' defined in NCR Ch.1 App.1. Checking will be by comparison to spare parts supplied by the manufacturer's official agent or by any other means necessary to ensure compliance.

d) Homologation papers, including VO, VK or ES extensions, will not be accepted as proof of specification of any components.

### 5.2: GENERAL DESCRIPTION

The Toyota MR2 Championship is open to competitors participating in the normally aspirated UK and Japanese domestic models of the mk1, mk2 and mk3 Toyota MR2. All vehicles must be of sound construction and mechanical condition and well maintained. There is no requirement for an MOT certificate, Road Fund License or Insurance.

Cars will run in three classes:-

Class A: Toyota MR2 mk1 - AW11

Class B: Toyota MR2 mk2 - SW20

Class C: Toyota MR2 Roadster / MR-S mk3 - ZZW30

The MR2 Championship regulations are intended to allow competitors to produce race cars that are safe, affordable and of a near identical level of performance, with the emphasis firmly placed on driver ability. Competitors are therefore asked to keep this in mind when building or modifying race cars and are encouraged to seek guidance from the Championship Co-ordinator where appropriate. A modification that gives a performance advantage at a high financial cost will almost certainly be illegal, or possibly outlawed in future regulations.

### 5.3: SAFETY REQUIREMENTS

#### 5.3.1 Roll Over Protection System (ROPS) (NCR Ch.7 App.13):

- Class A cars must use one of the following:
- A cage with a minimum of four points of attachment as shown in NCR Ch.7 App.13 diagram 10 with an additional compulsory diagonal member in the rear hoop. It must also be fitted with a forward-facing petty bar for a fifth point of attachment.
- A suitably certified / homologated roll cage (such as Safety Devices model TO11).
- A cage with six points of attachment as shown in NCR Ch.7 App.13 diagram 14/15.

All cages must be equipped with compulsory side entry bars on both the driver and passenger side of the vehicle.



For clarity, as class A cars are pre-1995, the following dimensions are the minima for all ROPS members: 38 x 2.5mm or 40 x 2.0mm (nearest imperial equivalents as shown in NCR Ch.7 App.3 Art.18.1c are also allowed).

- Class B cars must use a cage with six points of attachment as shown in MOTORSPORT UK drawing 14/15 equipped with compulsory side entry bars on both the driver and passenger side of the vehicle.

- Class C cars must use a cage with six points of attachment as shown in MOTORSPORT UK drawing 14/15 equipped with compulsory side entry bars on both the driver and passenger side of the vehicle. Optionally, an additional two points of attachment (bringing the total to eight) may be made at the front of the cabin as per MOTORSPORT UK diagram 20

For all classes: cages may only be secured by their mounting feet, and all mounting points must be contained within the confines of the cabin.

#### 5.3.2 Fire Extinguisher:

A plumbed in fire extinguisher as per NCR Ch.7 App 6 must be securely installed. Mounting location is free but competitors are advised to position the extinguisher in such a manner that it can be easily accessed by scrutineers, and armed / disarmed. Mechanical or electrical triggering mechanisms must be fitted such that the extinguisher can be operated both externally and by the driver whilst normally seated. The external fire extinguisher trigger must be situated adjacent to the external circuit breaker trigger.

#### 5.3.3 External Circuit Breaker (NCR Ch.7 App.5-Electrical Systems):

A circuit breaker must be fitted that when activated isolates all electrical circuits with the exception of those that operate a fire extinguisher. A trigger for the circuit breaker must be located externally, either at the base of the windscreen forward of the cabin, or on class A and B cars behind the flying buttresses rearward of the cabin.

#### 5.3.4 Identification Decals:

The external fire extinguisher trigger must be marked by the letter "E" in red inside a white circle of at least 10cm diameter with a red edge. The external circuit breaker trigger must be identified by a Red Spark on a White-edged Blue triangle (12cm base), and the 'On' and 'Off' positions clearly marked. If the triggers are installed behind the flying buttresses on class A and B cars then identification decals must be installed on both sides of the buttress.

#### 5.3.5 Red Warning (Rain):

As per NCR Ch.7 App.5 Art.6, all classes must have one of the following installed:

- A single high intensity red LED warning light located within 10cm of the centre line of the vehicle. The original equipment high level brake light on Class B cars may be used for this purpose.
- Two high intensity red LED warning lights equally located about the centre line of the vehicle.

#### 5.3.6 Harness and Seat:

A minimum four-point harness as per NCR Ch.7 App.7 must be installed. A six point harness is strongly recommended. A non-reclining competition seat as per NCR Ch.7 App.7 Art.2 must be fitted.

#### 5.3.7 Towing Eyes: NCR Ch.12 App.13 Art.1.3 & 1.4

Substantial towing eyes with an internal diameter of at least 60mm must be fixed securely to the main structure of the vehicle, front and rear, within the confines of the body. They may be of a rigid or flexible material and must be of a bright contrasting colour.

#### 5.3.8 Locking Mechanisms:

The driver and passenger interior door locks must be disconnected and rendered inoperable from inside the vehicle - they may still operate externally using a key. Central locking switches must be disabled. The original equipment catches for the bonnet and engine bay cover must be removed and these areas must be secured in the closed position using only externally accessible bonnet pins.



#### 5.4: GENERAL TECHNICAL REQUIREMENTS & EXCEPTIONS

All cars must comply with the requirements of NCR Ch.7 unless otherwise specified within these technical regulations. All vehicles must be of sound construction and mechanical condition and be well maintained. There are no requirements for vehicles to meet MOT standards. Exceptions to some regulations may be made to accommodate drivers with disabilities but must be agreed with the Championship Co-ordinator.

#### 5.5: CHASSIS

No chassis stiffening is permitted except that derived from installation of the roll cage. Seam welding of the shell is prohibited. Only original equipment factory fitted strut braces may be installed.

#### 5.6: BODYWORK

##### 5.6.1. Windows:

All windows must be installed. The front windscreen may be of original equipment specification laminated glass or clear polycarbonate of at least 5mm thickness. All other windows may be clear polycarbonate of at least 4mm thickness or original specification glass. It is permitted to install vents and / or slider kits to the side windows. The addition of a colourless safety film to the glass is permitted. Glass sunroof or T-bar panels are not permitted and must be removed or replaced with a non-shattering material, as per NCR Ch.12 App.13 Art.11.8. If installed, a sunroof must be firmly secured in the closed position. Electric window winding mechanisms may be replaced by original equipment manual winding mechanisms or removed. The driver and passenger door windows may remain operable or disabled and pinned in the closed position.

##### 5.6.2. Mirrors:

An interior rear view mirror must be installed on the centre line of the windscreen in the original location. This may be a standard or aftermarket mirror. Additional rear view mirrors may be installed on the inside of the windscreen provided that they do not impede the view of the driver or any mandated video recording equipment. The original equipment wing mirrors must be retained. Factory fitted folding wing mirrors must have the facility to retract electrically rendered inoperable.

##### 5.6.3. Interior:

With the exception of the original dashboard and instrument binnacle, all interior systems and trim may be removed. This includes (but is not limited to) carpets, sound deadening material, roof lining, heating, ventilation and air conditioning system, audio equipment, alarm systems, passenger seat, centre console, glove box and centre tunnel cover. Material may be removed from the dashboard only to allow fitment of the roll cage. If the interior door panels are removed, they must be replaced with sheet material - this must be executed to a high standard with no sharp edges and a smooth finish. The standard toolkit must be removed. The factory supplied "spacesaver" spare wheel may be removed, retained or replaced with a full-size standard wheel and tyre fixed in the standard location using either the original equipment fixing or a suitable metal plate and heavy duty bolt. Additional instruments are permitted. Steering wheels are free. Airbags must be removed. An effective windscreen demisting solution must be installed.

##### 5.6.4. Exterior:

No modification is permitted to the outer skin of any body panel by the addition, removal or deformation of material. Inner webbing or strengthening material may be removed, providing that this does not compromise the integrity of the outer skin. Replacement body panels must maintain the original shape and appearance but may be constructed of either original material or fibreglass.

- Class A and B cars may use any rear spoiler design originally factory fitted to their chassis or remove the spoiler entirely. Fibreglass replicas to the original equipment design may also be used.

-Class B cars may use a rectangular bracket manufactured from 2mm thick aluminium, 45mm wide, 385mm long. 2x 7mm I/D holes positioned 22.5mm from either end on the centreline of the component. All corners radius to 5mm. 1x 90deg bend 45mm from one end to form a component that's 340mm long to secure the underside of the front bumper. The bent 90deg end must be mounted to the front under chassis TOW point, via a pre-existing M6 threaded hole. The other must be mounted to the rear outermost front undertray fixing on the trailing edge of the front bumper splitter using 1x M6 nut and bolt.



- Class C cars may be fitted with front and rear bumper extensions, side skirts and spoilers provided that these parts were originally supplied as Toyota dealer fit options. Fibreglass replicas to the original equipment design may also be used. An original equipment hardtop or aftermarket fibreglass replica may be securely bolted in place using the original fixing points and steel brackets.

For all Classes, the bonnet, engine bay cover and boot lid must follow the vehicles original shut lines and must not have any non-standard gaps at their edges when fully closed. The fitment of tape, sealant or addition of any material to close body gaps is prohibited. The original number of wiper arms and blades must be retained and be fully functional but are otherwise free. Washer pump, bottle, piping and nozzles may be removed. All weather strips and channels must be retained.

## 5.7: ENGINE

### 5.7.1 Permitted Engines:

All classes must be fitted with the original factory engine as listed below. Where an engine is sourced from a different Toyota model, it must be of identical specification.

- Class A: Toyota 4AGE 1.6 litre or Toyota 1ZZFE 1.8 litre
- Class B: Toyota 3SGE 2.0 litre excluding BEAMS VVTI variant
- Class C: Toyota 1ZZFE 1.8 litre

If the following regulations do not explicitly specify that a part may be used or modification made then you should work on the principle that it cannot. It is the competitors responsibility to ensure that no prohibited parts have been used or modification carried out regardless of who has assembled the engine. In all instances, Toyota's workshop manuals will be used for reference. Where parts are specified in Toyota workshop manuals as being available from Toyota and used in the normal repair of an engine then such parts shall be considered standard. All classes are permitted to use cast 0.5mm oversized standard or pattern part pistons and to rebore engine blocks to suit. Forged pistons are not permitted

Class A: May run either standard Toyota 4AGE cams or Piper TOY16VBP285 cams. Valve springs are free. Cam pulleys are free and may be adjustable. Shimless buckets may be used in place of standard shims and buckets. Fuel pressure regulator is free. Crankshaft main and big end bearings are free. No other modifications are permitted beyond the repair or adjustment specified by the manufacturers workshop manual. Standard or standard pattern parts to original specification must be used. All covers must be retained. If using a 1ZZFE engine, all engine regulations are as class C.

Class B: No modifications are permitted beyond the repair or adjustment specified by the manufacturers workshop manual. Standard or standard pattern parts to original specification must be used. Crankshaft main and big end bearings are free. All covers must be retained.

Class C: Other than those detailed below for cars equipped with Sequential Manual Transmission systems, no modifications are permitted beyond the repair or adjustment specified by the manufacturers workshop manual. Standard or standard pattern parts to original specification must be used. Crankshaft main and big end bearings are free. All covers must be retained. For cars equipped with Sequential Manual Transmission systems, the flywheel is free and the throttle stop for the drive-by-wire system may be removed from the throttle body.

### 5.7.2 Location:

Position and mounting method must be standard for the model being raced. Bushes may be standard or polyurethane. No additional engine or transmission supports may be fitted.

### 5.7.3 Oil / Water Cooling:

Coolant radiators must remain standard in capacity and position but are otherwise free. Oil coolers are only permitted if standard for the model being raced.

### 5.7.4 Induction Systems:

Forced induction is not permitted. The induction system up to but not including the throttle body is free and must be contained within the engine bay. Class A cars may also use the boot area. Any ducting must remain within the confines of the body. The crankcase breather may vent directly to a catch can. No other modifications are permitted.

### 5.7.5 Exhaust Systems:



Exhaust systems must exit at the rear of the vehicle. Class A and B cars must retain the standard exhaust manifold which may not be modified. Class C cars: exhaust manifold is free but must remain compatible with the standard "B" pipe. Flanges must be to the same pattern as standard and occupy the same point in space. Class C cars must also be fitted with a catalytic converter which may be standard or aftermarket. For all classes, the remainder of the exhaust system including silencers is free. The use of heat wrap is permitted on any part of the exhaust system. Exhaust Gas Recirculation systems may be removed and / or rendered inoperable.

All vehicles must comply with the relevant maximum noise limits set out in NCR Ch.7 App.8

#### 5.7.6 Ignition Systems:

A standard ECU for the model being raced must be fitted and may not be modified. It is not permitted to modify the engine control signals in any way. Diagnostic connectors must remain present and functional. Class A and B cars must be capable of entering static timing mode. Class C car must be capable of communicating with a diagnostic scan tool.

Plug leads and spark plugs are free. For class A and B cars, base ignition timing must be set at no more than 13 degrees before top dead centre.

#### 5.7.8 Fuel Delivery Systems:

It is permissible to replace the fuel pump, fuel lines and filter with standard parts only. It is permitted to add a dry break fuel sampling solution as described in NCR Ch.7 App.4 Art.6

## 5.8: SUSPENSION

### 5.8.1. Permitted Modifications:

All Classes: The original suspension configuration must be retained. Anti-roll bars are free but must not be adjustable by the driver whilst seated. Whiteline adjustable camber bolts ~~supplied by the Championship Organiser~~ and Toyota offset camber bolts may be used. Standard or polyurethane suspension bushes are permitted. It is permitted to alter the ride height. No part of the car excluding the exhaust system may be below a horizontal plane passing 65mm above the ground, the car being in normal racing trim and the driver being seated in full race gear. The vehicle may be stationary or moving during any testing.

Class A Cars: Must run either of the following:

Dampers are free but must be of the same type as originally fitted and offer no adjustment that was not previously available. Damper bumpstops are free but must be fitted. Uprated / lowered springs are permitted provided that they are the same outside diameter of the standard coil and are made from one continuous length of wire. Adjustability of suspension geometry is limited to that provided by the vehicle manufacturer for the original suspension except camber, which is free. Drop links are free. Rear tie rods are free.

or:

BC Racing BR series type RA adjustable coilover kit comprising dampers, springs and top mounts. Spring rates must be 4kg/mm front and 6kg/mm rear. Only the adjustment made by the original suspension components and the coilover kit may be made except camber, which is free. Drop links are free. Rear tie rods are free. No component may be modified or omitted.

Class B Cars: Dampers may be only of the following type:

Standard Toyota

Bilstein Toyota (Black)

Bilstein B6 (Yellow)

It is permitted to brace the drop link mount by welding a tab between the top of the mount and the lower spring platform. No other modification may be made to the Bilstein dampers. Standard Toyota dampers may have their oil changed and the specification of that oil is free - no other modifications are permitted. Damper bumpstops are free but must be fitted. Uprated / lowered springs are permitted provided that they are the same outside diameter of the standard coil and are made from one continuous length of wire. Adjustability of suspension geometry is limited to that provided by the vehicle manufacturer for the original suspension except camber is free. Drop Links are free.

Class C Cars: Must run either of the following:

Dampers are free but must be of the same type as originally fitted and offer no adjustment that was not previously available. Damper bumpstops are free but must be fitted. Uprated / lowered springs are permitted provided that they



are the same outside diameter of the standard coil and are made from one continuous length of wire. Adjustability of suspension geometry is limited to that provided by the vehicle manufacturer for the original suspension except camber, which is free. Drop links are free.

or:

BC Racing BR series type RA adjustable coilover kit comprising dampers, springs and top mounts. Spring rates must be 5kg/mm front and 7kg/mm rear. Only the adjustment made by the original suspension components and the coilover kit may be made except camber, which is free. No component may be modified or omitted. Drop links are free.

#### 5.8.2. Prohibited Modifications:

Modifications to the suspension pick-up points are prohibited; this includes the slotting of suspension strut mounting points. Any modification which prevents a wheel from reach the standard fully dropped position is prohibited.

#### 5.8.3. Wheelbase and Track:

The wheelbase and track must be standard for the model being raced.

### 5.9: TRANSMISSION

#### 5.9.1. Permitted Modifications.

Driveshafts are free.

Class A must use a Toyota C50, C52, C56, C63, C65 or C66 Gearbox with either a factory open differential or factory torsen type limited slip differential.

Class B must use a Toyota S54 Gearbox with either a factory open differential or factory torsen type limited slip differential. It is permitted to use the factory torsen type limited slip differential from a Class C gearbox.

Class C must use a Toyota C56, C63, C65 or C66 Gearbox with either a factory open differential or factory torsen type limited slip differential.

Where more than one gearbox type is listed, parts from any of the gearboxes may be used in combination. Gears must be standard Toyota parts to the ratios specified in 5.9.3 but otherwise components are free.

#### 5.9.2. Prohibited Modifications.

Standard flywheel only is permitted and may not be modified in any way. Only one clutch plate is permitted. The use of electronic traction control devices is prohibited. Any device or modification that alters the throw of the gear lever (such as a short shifter) is prohibited.

#### 5.9.3 Transmission and Drive Ratios.

Class A must use the following ratios:

1st - 3.545 or 3.166

2nd - 1.904

3rd - 1.392 or 1.310

4th - 1.031 or 0.969

5th - 0.815

6th - 0.725

Final Drive - 4.312 or 4.058 or 3.941 or 3.722

Class B must use the following ratios:

1st - 3.285

2nd - 1.960

3rd - 1.322

4th - 1.028

5th - 0.820

Final Drive - 4.176 or 3.944

Class C must use the following ratios:

1st - 3.166



2nd - 1.904  
3rd - 1.392 or 1.310  
4th - 1.031 or 0.969  
5th - 0.815  
6th - 0.725  
Final Drive - 4.312 or 3.941

## 5.10: ELECTRICS

### 5.10.1 Exterior Lighting.

All classes must have standard headlights fitted and fully operational in the stock location. Class A and B cars must be capable of fully raising and lowering the headlamps using the standard motors, and they must be secured against glass breakage using tape or transparent film as per NCR Ch.12 App.13 Art.11.5. Class C cars have plastic lenses and therefore do not require tape or film. Front and rear sidelights and indicators are free but must be fitted in the stock location and be fully operational. Side repeaters need not function and can be removed. Rear light clusters are free but must be fitted in the stock location and the brake lights contained within them must illuminate without delay when the brake pedal is pressed. High level centre brake lights need not function and can be removed. Bulbs may be incandescent or LED. High Intensity Discharge lamps are not permitted. Front fog lights must be removed. Integral rear fog lights must be rendered inoperable.

In the event of a night race, a pair of auxiliary forward facing spotlights may be fitted to the front of the vehicle.

### 5.10.2 Battery.

A Battery must be fitted of such capacity that it is capable of repetitively starting the vehicle. The location and type of the battery is free, subject to Event the criteria set down in NCR Ch.7 App.5.

5.14. No external batteries may be used.

5.10.3 Generator. A fully working standard alternator must be fitted and electrically connected so that the standard battery charging function is providing a charge to the onboard battery. The system voltage when measured at the battery terminals must 13v or greater when the engine is running.

## 5.11: BRAKES

### 5.11.1 Permitted Modifications.

Brake pads must retain their original shape but material choice is free. Standard rubber brake hoses may be replaced with stainless steel braided items. Deformation or removal of the back plates is permitted. The handbrake must remain cable operated and functional. Additional brake ducting is permitted within the overall periphery of the bodywork. Discs may be replaced by standard or standard pattern parts.

Class A - ABS is not permitted.

Class B may remove factory fitted ABS systems and replace them with standard non-ABS components or otherwise disable them electrically.

Class C may disable the factory fitted ABS system electrically but may not remove or modify any components.

### 5.11.2. Prohibited Modifications.

Discs may not be drilled or grooved. Any device that alters the brake bias is prohibited.

## 5.12: WHEELS / STEERING

### 5.12.1 Permitted Modifications.

Wheels may be standard for the model raced or aftermarket replacements to the same dimensions. Wheels may be refurbished / repainted. Wheel nuts must be steel. Steering wheel is free and may be removable. It is recommended that the steering lock is rendered inoperative.

Class A: Standard non-power assisted steering rack only.

Class B: Either standard non-power assisted steering rack or standard power assisted system may be used. If the power assisted system is used all components must remain in place, but the power assist may be rendered electrically inoperable.



Class C: Standard power assisted system must be used. All components must remain in place, but the power assist may be rendered electrically inoperable.

#### 5.12.2 Prohibited Modifications.

It is not permitted to alter the wheels by removal of material. Wheel weights may be added for balancing only. Magnesium wheels are not permitted.

#### 5.12.3 Dimensions:

Class A: 5.5" x 14" or 6 x 14", PCD 4 x 100, Offset ET35 - ET45 or Front 6" x 15", Rear 6.5" x 15", PCD 4 x 100, Offset ET45

Class B: Front 6" x 15", Rear 7" x 15", PCD 5 x 114.3, Offset ET45

Class C: Front 6" x 15", Rear 6.5" x 15", PCD 4 x 100, Offset ET45

Class A must use either 14" or 15" wheels. It is not permitted to use the two sizes in combination.

### 5.13: TYRES

#### 5.13.1 Specification.

The control tyre is the Toyo R888R in GG (Medium Hard) compound. No alteration to the manufacturers specification is permitted, including but not limited to the use of tyre heating / heat retention devices, tyre treatments and compounds cutting, regrooving, buffing or in any other way modifying the tread pattern. The manufacturers data may not be removed from the sidewall of the tyre and must remain visible at all times. Only Toyo tyres purchased from the nominated supplier may be used.

#### 5.13.2 Sizes.

Class A: Front and rear: 185/60/14 or Front 195/50/15; Rear 205/50/15

Class B: Front 195/55/15 or 195/50/15; Rear 225/50/15

Class C: Front 195/50/15; Rear 205/50/15

#### 5.13.3 Nominated Supplier.

Rogue Motorsport Ltd, Units 5 & 6 Blue Lias Industrial Estate, Rugby Road, Stockton, CV47 8HN

Telephone 01926 810104, <http://www.roguemotorsport.com>

### 5.14: VEHICLE WEIGHT

Class A: 1000kgs

Class B: 1175kgs (172bhp engine)

1125kgs (158bhp engine)

Class C: 1000kgs (Equipped with manual transmission)

975kgs (Equipped with sequential manual transmission)

All weights are minimums and include the driver in full racing gear, as measured at the end of a qualifying session or race. Competitors are reminded that the calibrated scales presented at the circuit are considered definitive and are encouraged to check their weights at every round.

Ballast is permitted and must be located in the passenger area of the car as per NCR Ch.7 App.2 Art.19. It may be bolted to the original passenger seat mounting points.

### 5.15: FUEL TANK / FUEL

#### 5.15.1 Type.

The standard fuel tank must be used. Standard or aftermarket fittings and hoses may be used.

#### 5.15.2 Location



The fuel tank must be in the standard location.

#### 5.15.3 Fuel

Only petrol as defined in NCR Ch.8 App.1 Art.1.7a and complying with BS4040, BSEN228 or BS7800 may be used; fuel which exceeds the stated RON (max) levels in NCR Ch.8 App.1 Art.1.7a is **prohibited even if it is sold/promoted as being legal for UK Competition** and/or obtainable from 'roadside' pumps. The use of additives by competitors which boost the octane rating (RON) in any petrol is prohibited. At the end of practice and the race at least 3 litres of petrol from the tank of the competing car must be available to the scrutineers for analysis. Compliance with minimum weight for the car will be taken before the petrol is removed

### 5.16: NUMBERS & CHAMPIONSHIP DECALS

#### 5.16.1 Positions

Class A and B: Fluorescent yellow race numbers with a height of 200mm and a stroke width of at least 20mm must be located in the rear quarter windows on both sides of the car.

Class C: Fluorescent yellow race numbers with a height of 200mm and a stroke width of at least 20mm must be located on a black background in the lower rear quarter of the hardtop on both sides of the car or on both doors if a hardtop is not fitted.

All Classes: Fluorescent yellow race numbers with a height of 150mm and a stroke width of at least 15mm must be located on the passenger side of the front windscreen no closer than 50mm below the bottom edge of the sunstrip and 50mm from the side edge of the windscreen.

750 Motor Club decals must be affixed prominently. Championship sponsor decals must be affixed in the positions detailed on any diagram supplied with those decals. 750 Motor Club and Championship sponsor decals must take precedence over any other decals or livery. Competitors displaying decals that conflict with the Championship sponsors may be required to remove them. Failure to comply will render the vehicle and driver ineligible to race. The Championship coordinator's decision is final.

#### 5.16.2 Suppliers

Sponsor and club decals will be available at the first championship race in which the vehicle is entered.